

miniwelder geo2



To the product



Technical data

Voltage	120 V; 230 V	
Frequency	50/60 Hz	
Power	800 W	
Speed	0.4-7.5 m/min	1.31-24.6 ft/min
Temperature	60-480 °C	140.0-896.0 °F
Hot wedge length	50 mm	1.96 in
Hot wedge width	36 mm	1.41 in
Hot wedge material	Copper; Stainless steel	
Max. overlap	100 mm	3.93 in
Welding materials	CSPE; FPO; HDPE; LDPE; LLDPE; PE; PP; PVC	
Weldable material thicknesses	0.5-1.5 mm	19.68-59.05 mil
LQS	No	
Length	228.0 mm	8.97 in
Width	228.0 mm	8.97 in
Height	170.0 mm	6.69 in
Weight	3.9 kg	8.59 lb
Approvals	CB Certification; CE	
Protection class	I	
Country of origin	CN	

miniwelder geo2

Scope of delivery

Wire brush, brass; Allen wrench 3 mm; Aluminum case

Product items

125.503	miniwelder geo2, 120V/800W, copper wedge, US plug
154.880	miniwelder geo2, 230V/800W, copper wedge, EU plug
154.884	miniwelder geo2, 230V/800W, steel wedge, EU plug